

Figure 1: Control Plane Initial Attach Procedure + Default Bearer Creation






Figure 2: MME detailed behaviour: Default Bearer Creation

MME

MME application or default MME parameter

SIAP

SIAP provided parameter

NAS

NAS provided parameter

S6A

HSS provided parameter

SI1

S1-P-GW provided parameter

SCTP

SCTP provided parameter

Optional

Optional parameter




Figure 3: MME detailed behaviour: Default Bearer Rejected (S6A Authentication Failure)




Figure 4: MME detailed behaviour: Default Bearer Rejected (S6A Update Location Failure)




Figure 5: MME detailed behaviour: Default Bearer Rejected (S-GW Failure)

<b>MME</b>	MME application or default MME parameter
<b>SLAP</b>	SLAP provided parameter
<b>NAS</b>	NAS provided parameter
<b>S6A</b>	HSS provided parameter
<b>S11</b>	S+P-GW provided parameter
<b>SCTP</b>	SCTP provided parameter
<i>Optional</i>	Optional parameter




Figure 6: MME detailed behaviour: Default Bearer Rejected (eNB Reject or Failure)

MME	MME application or default MME parameter
SIAP	SIAP provided parameter
NAS	NAS provided parameter
S6A	HSS provided parameter
S11	S1-P-GW provided parameter
SCTP	SCTP provided parameter
Optional	Optional parameter