

MAC-PHY Interface

Advisor : Cheng, Ray-Guang

Student : BMW LAB

Date : 2017/04

Outline

- **Downlink Control Information**
 - Different between LTE and NB-IoT
 - Detail Field Summary for DCI N0 N1 N2
 - NB-IoT DCI Structure example
- **FAPI-Style Interface for NB-IoT based on OAI**
 - 5 Step API
 - OAI old primitives in FAPI-Style interface
- **eNB MAC-PHY Interface in OAI**
 - Top level primitives
 - Detail definition to OAI primitive (by blocks)
 - Random Access
 - Config
 - Scheduling

Outline

- **Downlink Control Information**
 - Different between LTE and NB-IoT
 - Detail Field Summary for DCI N0 N1 N2
 - NB-IoT DCI Structure example
- FAPI-Style Interface for NB-IoT based on OAI
 - 5 Step API
 - OAI old primitives in FAPI-Style interface
- eNB MAC-PHY Interface in OAI
 - Top level primitives
 - Detail definition to OAI primitive (by blocks)
 - Random Access
 - Config
 - Scheduling

DCI in LTE vs NB-IoT

- ➔ In LTE, the DCI's length should be determined by the bandwidth and the transmission mode (FDD or TDD), so the same format of the DCI may have the different length.
- ➔ There is no TDD mode in NB-IoT.
- ➔ DCI N1 may separate to 3 types of field.
- ➔ In NB-IoT, the length of DCI is fixed to
 - Format N0, N1 – 23bits
 - Format N2 – 15 bits

DCI N0 – 23 bits

Field	Number of bits
Flag for format N0/format N1 differentiation	1
Subcarrier indication	6
Resource assignment	3
Scheduling delay	2
Modulation and coding scheme	4
Redundancy version	1
Repetition number	3
New data indicator	1
DCI subframe repetition number	2

DCI N1 – 23 bits

For Initiated Random Access
CRC is scrambled with C-RNTI

Field	Number of bits
Flag for format N0/format N1 differentiation (set to 1)	1
NPDCCH order indicator (set to 1)	1
Starting number of NPRACH repetitions	2
Subcarrier indication of NPRACH	6
All the remaining bits (set to 1)	13

For Random Access MSG 2
CRC is scrambled with a RA-RNTI

Field	Number of bits
Flag for format N0/format N1 differentiation (set to 1)	1
NPDCCH order indicator (set to 0)	1
Scheduling delay	3
Resource assignment	3
Modulation and coding scheme	4
Repetition number	4
Reserved	5
DCI subframe repetition number	2

For Otherwise

Field	Number of bits
Flag for format N0/format N1 differentiation (set to 1)	1
NPDCCH order indicator (set to 0)	1
Scheduling delay	3
Resource assignment	3
Modulation and coding scheme	4
Repetition number	4
New data indicator	1
HARQ-ACK resource	4
DCI subframe repetition number	2

DCI N2 – 15 bits

Field	Number of bits
Flag for paging/direct indication differentiation (set to 1)	1
Resource assignment	3
Modulation and coding scheme	4
Repetition number	4
DCI subframe repetition number	3



NB-IoT DCI structure example

```
/// DCI Format Type 0 (5 MHz,TDD0, 27 bits)
struct DCI0_5MHz_TDD0 {
    /// type = 0 => DCI Format 0, type = 1 => DCI Format 1A
    uint32_t type:1;
    /// Hopping flag
    uint32_t hopping:1;
    /// RB Assignment (ceil(log2(N_RB_UL*(N_RB_UL+1)/2)) bits)
    uint32_t rballocc:9;
    /// Modulation and Coding Scheme and Redundancy Version
    uint32_t mcs:5;
    /// New Data Indicator
    uint32_t ndi:1;
    /// Power Control
    uint32_t TPC:2;
    /// Cyclic shift
    uint32_t cshift:3;
    /// DAI (TDD)
    uint32_t ulindex:2;
    /// CQI Request
    uint32_t cqi_req:1;
    /// Padding to get to size of DCI1A
    uint32_t padding:2;
} ? end DCI0_5MHz_TDD0 ? __attribute__((packed));

typedef struct DCI0_5MHz_TDD0 DCI0_5MHz_TDD0_t;
#define sizeof_DCI0_5MHz_TDD0_t 27
```


```
00001: /// DCI Format Type N0
00002: struct DCIN0 {
00003:     /// type = 0 => DCI Format N0, type = 1 => DCI Format N1
00004:     uint32_t type:1;
00005:     /// Subcarrier indication
00006:     uint32_t scind:6;
00007:     /// Resource Assignment (RU Assignment)
00008:     uint32_t ResAssign:3;
00009:     /// Modulation and Coding Scheme and Redundancy Version
00010:     uint32_t mcs:4;
00011:     /// New Data Indicator
00012:     uint32_t ndi:1;
00013:     /// Scheduling Delay
00014:     uint32_t Scheddly:2;
00015:     /// Repetition Number
00016:     uint32_t RepNum:3;
00017:     /// Redundancy version for HARQ (only use 0 and 2)
00018:     uint32_t rv:1;
00019:     /// DCI subframe repetition Number
00020:     uint32_t DCIRep:2;
00021: } ? end DCIN0 ? __attribute__((packed));
00022:
00023: typedef struct DCIN0 DCIN0_t;
00024: #define sizeof_DCIN0_t 23
00025: }
```


Outline

- Downlink Control Information
 - Different between LTE and NB-IoT
 - Detail Field Summary for DCI N0 N1 N2
 - NB-IoT DCI Structure example
- **FAPI-Style Interface for NB-IoT based on OAI**
 - 5 Step API
 - OAI old primitives in FAPI-Style interface
- eNB MAC-PHY Interface in OAI
 - Top level primitives
 - Detail definition to OAI primitive (by blocks)
 - Random Access
 - Config
 - Scheduling

FAPI-Style Interface


➔ 5 steps API (general)



OAI old primitives in FAPI-Style interface

MAC module

Interface



Outline

- Downlink Control Information
 - Different between LTE and NB-IoT
 - Detail Field Summary for DCI N0 N1 N2
 - NB-IoT DCI Structure example
- FAPI-Style Interface for NB-IoT based on OAI
 - 5 Step API
 - OAI old primitives in FAPI-Style interface


● eNB MAC-PHY Interface in OAI

- Top level primitives
- Detail definition to OAI primitive (by blocks)
 - Random Access
 - Config
 - Scheduling

eNB MAC-PHY interface

➔ Top level function (detail)

– Openair2/PHY_INTERFACE/defs.h




Note:

1. Add **phy_config_MIB_eNB** in PHY Config block
2. **get_eNB_UE_stats** should be in Scheduling block
3. **Helper Functions** should be defined in each side of the process (MAC or PHY)
4. **SR_indication** is not used for NB-IoT.
5. **fill_rar** will disappear on the new interface, this will be a normal DCI (with RA-RNTI) sent down by MAC.



BMW LAB

Random Access



➔ [Modify] Initiate_ra_proc:

- Function to indicate a received preamble on PRACH. It initiates the RA procedure.
- The preamble format has changed, and use the time and frequency domain to indicate the preamble.


➔ [Modify] fill_rar:

- Function in eNB to fill RAR pdu when requested by PHY. This provides a single RAR SDU for the moment and returns the t-CRNTI.
- The field of DCI for RAR and the RAR grant for MSG3 has changed.

➔ [Re-use] cancel_ra_proc:

- Function to indicate a failed RA response. It removes all temporary variables related to the initial connection of a UE.

initiate_ra_proc



Entry Point:


After `rx_prach()` in `prach_procedures` triggered by `phy_procedures_eNB_common_RX`, this primitive will start to initial a Random Access procedure.

- [Modify] `RA_template_NB` structure :
 - Preamble_freq domain[48]
 - Preamble_time domain
 - CE_level = 0 , 1 , 2
 - CE_level Mode A = 0,1 , Mode B = 2.

fill_rar

Entry Point

In **pdsch_procedures**, this function will run if **ra_flag** set to 1.




- **[Modify]** RAR PDU content
- **[Modify]** Fill RAR will disappear on the new interface, this will be a normal DCI (with RA-RNTI) sent down by MAC.


Table 6-2: Random Access Response Grant Content field size

DCI contents	CEmodeA	CEmodeB
Msg3 PUSCH narrowband index	N_{NB}^{index}	2
Msg3 PUSCH Resource allocation	4	3
Number of Repetitions for Msg3 PUSCH	2	3
MCS	3	0
TBS	0	2
TPC	3	0
CSI request	1	0
UL delay	1	0
Msg3/4 MPDCCH narrowband index	2	2
Zero padding	$4 - N_{NB}^{index}$	0
Total Nr-bits	20	12


CEmodeA



CEmodeB



cancel_ra_proc



Entry point

In `phy_procedures_eNB_uespec_RX`, this function will run if


- `maxHARQ_Msg3Tx` reached, abandoning RA procedure for UE
- one-shot msg3 detection by MAC: empty PDU

In `pdsch_procedures`, this function will run if

- Max user count reached

- **[Delete]** It's no need for NB-IoT, MAC will definitely know that retransmission has been exhausted.

PHY Config



- ➔ **[Delete]** `Phy_config_sib1_eNB`:
 - SI window size & SI period
- ➔ **[Modify]** `Phy_config_sib2_eNB`:
 - Configuration of most frame parameters & channel
- ➔ **[Modify]** `Phy_config_dedicated_eNB`:
 - Configure `PHY_VARS_eNB` with components of `physicalConfigDedicated`
- ➔ **[Add]** `Phy_config_mib_eNB`:
 - Pass the important configuration from MIB for PHY.

phy_config_sibx_eNB

Entry Point

In **phy_config_sibx_eNB**, functions will be called by

- **rrc_mac_config_req** call in the initial statement.

• phy_config_sib1_eNB


- Use for TDD mode primitive (not use in NB-IoT)

• phy_config_sib2_eNB


- [Modify] PRACH config -> NPRACH config
- [Modify] PDSCH config -> NPDSCH config
- [Modify] PUSCH config -> NPUSCH config
- Modify the terms which are NB-PHY implementation needed according to the Physical layer design.
- Reference to TS36.331-d30 Chapter 6.7.3.1
【SystemInformationBlockType2-NB】

• phy_config_sib13_eNB

- Multicast mode not be used in NB-IoT




Scheduling



- ➔ **[Re-use]** `get_dci_sdu`:
 - retrieve result of scheduling (DCI) in current subframe. Can be called an arbitrary number of times after `eNB_dlsch_ulsch_scheduler`.
- ➔ **[Re-use]** `get_dlsch_sdu`:
 - PHY get downlink data from MAC layer.
- ➔ **[Re-use]** `eNB_dlsch_ulsch_scheduler`:
 - Function to trigger the eNB scheduling procedure.
- ➔ **[Modify]** `NB_rx_sdu`:
 - MAC get Uplink data from PHY layer.

rx_sdu




Entry Point:

When **rx_tx** thread created, this function will run if this subframe is set for **uplink scheduled**. After passing some limitation (check if is uplink scheduled, if turbo code can be decoded correctly...), this function will start to transport data from PHY to upper layer.


- [Re-use]mac_eNB_rrc_ul_in_sync:
 - Get UE context for RLF (check if out of sync) from RRC layer.
- [Re-use]parse_ulsch_header:
 - Parse uplink share channel header from MAC PDU.
- [Modify]receive_CE:
 - This part will change the correspond information determined by the case of Control Element(BSR,CRNTI...).
 - In NB-IoT, it will check **DPR (DV and PHR)** when **Msg3** receiving.
- [Modify]receive_sdu:
 - This part include receiving sdu by the case of **logical channel** to use different primitives to transport data to RLC or RRC.
 - Include **mac_rlc_data_ind()** **mac_rrc_data_ind()**
 - In NB-IoT, there is no DTCH channel for the case.

schedule_ulsch



Entry Point:

When **rtx** thread created, this function will run in subframe n for each subframe and it's set for **uplink scheduled**. This function will start to schedule UL data for schdled subframe(n+4).



Modify Item:

(1) Parameters Initialize

- delete parameters related to TPC & RBs

(2) ulsch_scheduler_pre_processor

- Resource Unit (RU) replace RBs in UL resource allocation
- PHR in Msg3 DPR header to decide mcs
- Modify MSC to TBS table defined in Rel.13 36.213.
- Calculate how many Rus used for each UE


(3) delete any procedure not defined in NB-IoT

- ```
-CCE_allocation_infeasible()
-ComputeRIV() // For rbballoc in LTE
```

**(4) Modify related DCI setting:**

- No cqi\_req & Power Control(tpc) in NB-IoT
- resource allocation is different to LTE
- Modify cyclic shift defined in Table 10.1.4.1.2.3 TS 36.211 (OAI set cshift as fixed value 0)

# schedule\_ue\_spec



## Entry point:

In LTE, trigger downlink scheduler per subframe.

In NB-IoT, we only need to trigger downlink scheduler one time per PP (PDCCH period).

- [Modify] : dlsch\_scheduler\_pre\_processor
  - Need a new way to implement NB-IoT resource allocation.
- [Delete] TDD relative:
  - NB-IoT do not support TDD option.
- [Delete] CQI relative:
  - No CQI implementation in NB-IoT
- [Modify] Retransmission part:
  - This part need a new way to implement NB-IoT resource allocation
- [Modify] New transmission part:
  - This part need a new way to implement NB-IoT resource allocation
  - DTCH part is not support in NB-IoT C-Plane solution.
- [Modify] DCI
  - DCI have different format in NB-IoT. Add new DCI format N0, N1 and N2.